Supreme Touch



TECHNICAL SPECIFICATIONS

Country of Origin: Australia
Colours: 13 Standard

Yarn: 100% Soft Solution Dyed Nylon

Surface Texture: Cut Pile Twist

Gauge: 39.4/10cm (1/10th Gauge)

Thickness: 10.00mm

Pile Weight: 1530g/m²

Backing: Synthetic

Installation Method: Conventionally Laid

Type: Broadloom Carpet

Roll Size: 3.66
Secondary Backing: Synthetic
Pattern Repeat: Not Applicable

PERFORMANCE

Anti-Static: (AATCC 134) <3.5KV at 21°C & 20% Relative Humidity

Flammability: CRF 5.5kW/m2 (Conventionally Laid)~

Light Reflectance: Available on Request

Stain Resistance: Stain Block®

ACCS Rating: Residential Extra Heavy Duty & Stairs, Contract Medium Duty & Stairs (#14235)~

Australian Guarantee: 5 Year Contract Guarantee Available on Request*

Smoke Value: 234% minutes (Conventionally Laid)

SUSTAINABILITY

Accreditation: Manufactured under a quality, environmental and health and safety system certified

and complying with ISO 9001, ISO 14001 and AS 4801 by accredited certification

bodies.

PVC Minimisation: PVC Free



















Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpets must be installed in accordance with the latest AS2455 and any relevant GH Commercial Installation Instructions. ~Test results and certificates are available on request. *This guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee, please contact your GH Commercial Account Manager or our Head Office.



Supreme Touch



